Rec'd PCT/PT@ 25 JAN 2005

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau



(43) International Publication Date 12 February 2004 (12.02.2004)

PCT

(10) International Publication Number WO 2004/013892 A3

(51) International Patent Classification7: 61/35, 61/26

H01J 61/72,

(21) International Application Number:

PCT/IB2003/003129

(22) International Filing Date:

11 July 2003 (11.07.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

02078111.8

29 July 2002 (29.07.2002) EP


- (71) Applicant (for all designated States except US): KONIN-KLLJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): VOSSEN, Engelbertus, C., P., M. [NL/NL]; c/o Prof . Holstlaan 6,

NL-5656 AA Eindhoven (NL). STAATS, Cornelia, T. [NL/NL]; c/o Prof . Holstlaan 6, NL-5656 AA Eindhoven (NL). GEERDINCK, Leonie, M. [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). DE BEER. Esther [NL/NL]; c/o Prof . Holstlaan 6, NL-5656 AA Eindhoven (NL). SNLJKERS-HENDRICKX, Ingrid, J., M. [BE/BE]; c/o Prof . Holstlaan 6, NL-5656 AA Eindhoven (NL).

- VAN WERMESKERKEN, Stephanie, C.; Philips Intellectual Property & Standards, Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC. SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

[Continued on next page]

(54) Title: LOW-PRESSURE MERCURY VAPOR DISCHARGE LAMP



(57) Abstract: A low-pressure mercury vapor discharge lamp (1) has a discharge vessel (3) enclosing, in a gastight manner, a discharge space provided with a filling of mercury and a rare gas. The discharge vessel (3) comprises means for maintaining an electric discharge in the discharge space. A portion of the surface (15) of the discharge vessel (3) facing the discharge space is provided with a protective layer (16) comprising yttrium oxide or aluminum oxide and further comprises a borate and/or a phosphate of an alkaline earth metal and/or of scandium, yttrium, or a further rare earth metal. Preferably, the alkaline earth metal is calcium, strontium, and/or barium. Preferably, the further rare earth metal is lanthanum, cerium, and/or gadolinium. The lamp according to the invention has a comparatively low mercury consumption.

